

FLOW CONTROL

Fire Valves & Accessories



ALLOY F X F BOWL TYPE OIL FILTERS

CODE

- PRESSURE TESTED 2 BAR
- MAX WORKING TEMP. ALLOY BOWL 90°C
- MAX WORKING TEMP. TRANSPARENT BOWL 50°C

1/4" BSP	MF 6167
3/8" BSP	MF 6160
1/2" BSP	MF 6172
Spare 1/4" / 3/8" Filters Metal	MF 5160



FIRE VALVES - STANDARD BRASS FUSIBLE HEAD

F x F 3/8" / 10mm
Spare Fusible Heads

MF 1123
MF 1122



RESETTABLE REMOTE ACTING FIRE VALVE

- BS 5410 -1 & BS 799
- OFTEC APPROVED AND LISTED
- AVAILABLE IN TWO TEMP SETTINGS 66°C + 90°C ACTIVATIONS

1.5 mtr x 66°C 3/8" F x F	MF 6173
3.0 mtr x 66°C 3/8" F x F	MF 6174
6.0 mtr x 66°C 3/8" F x F	MF 6175
9.0 mtr x 66°C 3/8" F x F	MF 6176
15.0 mtr x 66°C 3/8" F x F	MF 6177
1.5 mtr x 90°C 3/8" F x F	MF 61739
3.0 mtr x 90°C 3/8" F x F	MF 61749
6.0 mtr x 90°C 3/8" F x F	MF 61759
9.0 mtr x 90°C 3/8" F x F	MF 61769



OIL CHECK VALVE

3/8" Female Brass Body c/w 8mm - 10mm Pipe Connection

FOL 4008