

ENGINE DRIVEN PUMPS

Diesel

Water

New Product



1" ENGINE DRIVEN UNLEADED TRANSFER PUMP

CODE

- FOR TRANSFERRING DIESEL OR CLEAN WATER.
- MAX. FLOW 125L/MIN. 1.6 LITRE UNLEADED PETROL TANK.
- TOTAL HEAD 20 METRES. SUCTION LIFT 9 METRES. DRY WEIGHT 17KGS.
- 4 STROKE ENGINE WITH RECOIL START. 1" HOSE TAILS & SUCTION STRAINER.
- DIMENSIONS 470MM H X 450MM W X 320MM D.

CTS 125ED

IF USED WITH NOZZLE/VALVE AS MEANS OF CONTROL, A PRESSURE RELIEF VALVE MUST BE USED OR WARRANTY VOID.

Optional Pressure Relief Valve

CTS 125EDP

NOTE: ALL MODELS MUST NOT BE RUN DRY

New Product



2" ENGINE DRIVEN UNLEADED TRANSFER PUMP

- FOR TRANSFERRING DIESEL OR CLEAN WATER.
- MAX. FLOW 500L/MIN. 2.5 LITRE UNLEADED PETROL TANK.
- TOTAL HEAD 26 METRES. SUCTION LIFT 7 METRES. DRY WEIGHT 22KGS.
- 4 STROKE ENGINE WITH RECOIL START. 2" HOSE TAILS & SUCTION STRAINER.
- DIMENSIONS 360MM H X 470MM W X 370MM D.

CTS 2500ED

IF USED WITH NOZZLE/VALVE AS MEANS OF CONTROL, A PRESSURE RELIEF VALVE MUST BE USED OR WARRANTY VOID.

Optional Pressure Relief Valve

CTS 2500EDP

NOTE: ALL MODELS MUST NOT BE RUN DRY