

**PTO
Pump & Compressors**

Water

Air



EOLOMATIC

IT IS THE BEST-SELLING TRACTOR PTO COMPRESSOR IN THE WORLD. IT IS A TWIN CYLINDER COMPRESSOR EQUIPPED WITH INCORPORATED MANOMETER AND ADJUSTABLE SAFETY VALVE FOR PRESSURE ADJUSTMENT. THE AIR LOCK (PIUSI PATENT) PROVIDES A CONTINUOUS AND CONSTANT FLOW FOR A BETTER USE OF COMPRESSED AIR WHEREVER YOUR TRACTOR MAY BE. THE EOLOMATIC COMPRESSOR IS DELIVERED READY FOR USE AND EQUIPPED WITH A 4M SPIRAL HOSE, CONNECTORS, INFLATION HEAD, ANCHOR CHAINS AND ABSORBER WITH KEY.



ST EXTRA - ST SUPERPIUSI PTO 500

IT IS THE FIRST PTO WASHING PUMP EVER BUILT IN THE WORLD. ROTARY, NO VALVES, SELF-PRIMING, EXTREMELY MAINTENANCE-FRIENDLY. THE PUMP IS DESIGNED FOR DIRECT CONNECTION TO POWER SOCKETS ON ANY TRACTOR. IT IS EQUIPPED WITH A STAINLESS STEEL SHAFT, INTEGRAL ROLL-SUPPORT IMPELLER AND SPECIAL SEAL (PIUSI PATENT). IT IS PRODUCED ON A LARGE SCALE, EVERY COMPONENT IS RIGOROUSLY CONTROLLED AND IT IS EXPORTED WHEREVER THERE IS NEED FOR A HIGHLY EFFICIENT WASHING POWER ALL OVER THE WORLD.

EXTRA - SUPERPIUSI EQUIPMENT

WASHING NOZZLE, SUCTION FILTER, Ø25 SUCTION CONNECTION AND Ø16 DELIVERY CONNECTION, PIPE-GRIP CLAMPS, ANCHOR CHAINS WITH KEY.

ST EXTRA - ST SUPERPIUSI EQUIPMENT

VERSIONS DELIVERED EQUIPPED AS ABOVE PLUS 3M SUCTION HOSE AND 7M DELIVERY HOSE.

PTO 500 EQUIPMENT

Ø50 FLANGE RUBBER HOSE HOLDER FOR SUCTION AND DELIVERY, FILTER, BRACKET, CHAINS WITH KEY. THIS MODEL IS ALSO DESIGNED FOR OPERATING WITH CARDAN SHAFTS OR PULLEYS, IN WHICH CASE THE PUMP IS FIXED BY MEANS OF THE BRACKET.



TECHNICAL INFORMATION

CODE

Description	Rpm	Flow Rate L/min Max	Bar Max	Weight Kg	
Eolomatic	300 ÷ 600	65 ÷ 130	10	10	850000
Extra	300 ÷ 600	50 ÷ 100	20	11.6	805000
ST Extra	300 ÷ 600	50 ÷ 100	20	14.5	800000
Superpiusi	300 ÷ 600	55 ÷ 110	25	11.6	806000
ST Superpiusi	300 ÷ 600	55 ÷ 110	25	14.5	801000
PTO 500	200 ÷ 800	100 ÷ 350	10	20.6	802000