

ELECTRONIC FLOW METERS

Remote Display Oval Gear Pulse Meters

Diesel Oil Rapsoil Urea Windscreen

New Product



DESIGNED AND REALISED TO BE USED WITH THE RANGE OF PULSE METERS. REMOTE INSTALLATION IS PROVIDED BY SIMPLY CONNECTING 2 WIRES. A LARGE SCREEN SIMULTANEOUSLY DISPLAYS THE QUANTITY DELIVERED AND THE NON-RESETTABLE TOTAL. THE REMOTE DISPLAY ALSO COMES WITH SOFTWARE APPLICATIONS FOR CALIBRATING FLOW METERS.

IT IS AVAILABLE BOTH AS A BASIC DISPLAY DEVICE AND AS A PULSE EMITTER. IT IS INDISPENSABLE WHEN THE RECEIVER ONLY RECOGNISES DISCRETE QUANTITIES OF PULSES.

THE REMOTE DISPLAY IS THE IDEAL ADDITION TO OUR SERIES OF PULSE METERS WHEREVER THE DISPLAY AND READING OF QUANTITIES DELIVERED ARE INDISPENSABLE, NOT DIRECTLY AT THE POINT OF INSTALLATION OF THE FLOW METERS, BUT OVER A DISTANCE.

WITH THEIR EASY INTERFACING MANAGEMENT SYSTEMS, PULSE TRANSMITTER MODELS CONNECTED TO REMOTE DISPLAY EXTEND THE FIELD OF APPLICATIONS OF PULSE METERS.

MULTI-FUNCTION DISPLAY

- 8 DIGITS RESETTABLE
- RESETTABLE TOTAL AVAILABLE
- 8 DIGITS NON-RESETTABLE TOTAL
- 5 DIGITS PARTIAL
- FLOW RATE
- FACILITY TO SET UNIT OF MEASURE
- FACILITY TO SET PULSE OUT
- CALIBRATION
- LOW BATTERY ICON



SPECIFICATIONS

SINGLE DISPLAY WITH 5 FIGURE PARTIAL TOTAL (H=11.5MM) FLOATING POINT (0.001 TO 99999) AND 8 FIGURE RESETTABLE TOTAL (H=5MM, FROM 1 TO 99999999)

- FRONT SEALING PLATE AND DISPLAY GUARD
- RESET BUTTON AND CALIBRATION
- BATTERY OR GRID POWERED
- REMOTE CONNECTION TO PULSE METER UP TO 15M
- PULSE OUT SET IN 1, 2, 10, 20, 50, 100 P/LITRE
- RESETTABLE TOTAL AVAILABLE
- DIFFERENT UNIT OF MEASUREMENT SETTING OPTION
- LOW BATTERY INDICATION
- FLOW RATE INDICATION

AVAILABLE MODELS

- ▲ REMOTE DISPLAY FOR DISPLAY ONLY
BATTERY POWERED DISPLAY 2 X 1.5V
- REMOTE DISPLAY WITH PULSE TRANSMITTER
- BATTERY POWERED 2 X 1.5V
OUTGOING SIGNAL TYPE: OPEN COLLECTOR
MAX 50V, 1.2 AMP, SINGLE CHANNEL.
- GRID POWERED 4 - 12VDC, 1.2 AMP
OUTGOING SIGNAL TYPE: OPEN COLLECTOR
MAX 50V, 1.2 AMP, SINGLE CHANNEL.
- TO SHOW REMOTELY THE QUANTITY DISPENSED. CONNECTED TO THE PULSE OUT VERSION (UP TO 100M) WITH THE RESET BUTTON SYNCHRONIZED (ONCE ONE DISPLAY IS RESET, THE SAME THING HAPPENS TO THE OTHER).

TECHNICAL INFORMATION

CODE

Description	Suitable for Pulse Meter	Versions	Weight Kg	Package mm	CODE
Remote Display K600/3	K600 Diesel	Display ▲	1.2	225x125x150	F1123300A
Remote Display K600/4	K600/4	Display ▲	1.2	225x125x150	F1123500A
Remote Display K700	K700	Display ▲	1.2	225x125x150	F1123600A
Remote Display Pulse out K600	K600 Diesel	Pulse out ■	1.2	225x125x150	F1175200A
Remote Display Pulse out K600/4	K600/4	Pulse out ■	1.2	225x125x150	F1175300A
Remote Display Pulse out K700	K700	Pulse out ■	1.2	225x125x150	F1175400A
Universal Display Pulse out	K200, K400, K600 Oil K600 Diesel, K600/4, K700	Pulse out ■	1.2	225x125x150	F00495010
Display Pulse in	For all Piusi Pulse out Remote Display	Pulse in ■	1.2	225x125x150	F00495020