

HOSES & ACCESSORIES

Couplings & Connectors



EMERGENCY BREAKAWAY COUPLING FOR FLAMMABLE LIQUIDS

CODE

- INTERNAL PRESSURE BALANCING CHAMBER PREVENTS 'LINE SHOCK' NUISANCE SEPARATIONS
- UNIT QUICKLY AND EASILY SNAPS BACK TOGETHER AFTER DRIVEAWAY BREAK
- SEPARATES AT LESS THAN 200LBS PULL FORCE TO MINIMIZE BACKLASH DAMAGE
- UNIQUE PRELOADED SHOCK ABSORBING WAVE SPRING MINIMIZES NUISANCE BREAKS
- HAS A UNIQUE VALVE TO STOP VAPOURS FROM ESCAPING AFTER A DRIVEAWAY

³/₄" Breakaway Coupling - Reusable
 1" Breakaway Coupling - Reusable

PF 652
PF 654



FLEXIBLE CONNECTORS

THIS RANGE OF FLEXIBLE CONNECTORS FEATURES CONVOLUTED STAINLESS STEEL PIPING, WELDED TO A RANGE OF STEEL END TERMINATIONS TO SUIT MOST COMMON PUMP INSTALLATIONS. ALSO AVAILABLE IS A NEW TYPE WHICH ARE CONSIDERABLY SHORTER TO ENABLE THEM TO BE COMPLETELY WITHIN THE PUMP HOUSING WHEN INSTALLED.

Tri-flange x Tri-flange 6"	KFC 6000
1.5 BSP Male x Tri-flange 6.75"	KFC 6750
1.5 BSP Female x Tri-flange 6.75"	KFC 6751
1.5 BSP Male x Tri-flange 4.5"	KFC 4500
1.5 BSP Female x Tri-flange 4.5"	KFC 4501
1.5 BSP Female x Oval-flange 5.75"	KFC 5750
Gasket	KFC 4498
Tri-flange only	KFC 4499