

# GAUGES

## Clock & Hydrostatic Gauges



### CLOCK GAUGES

CODE

EUROGAUGE FLOAT TYPE

2' x 1 1/2" BSP	<b>OAB 3002</b>
3' x 1 1/2" BSP	<b>OAB 3003</b>
4' x 1 1/2" BSP	<b>OAB 3304</b>
5' x 1 1/2" BSP	<b>OAB 3305</b>
6' x 1 1/2" BSP	<b>OAB 3309</b>
8' x 1 1/2" BSP Adjustable (cm Display)	<b>OAB 3308</b>
0' - 6' x 1 1/2" BSP Adjustable (0 - 6ft Display)	<b>OAB 3310</b>
4' x 1 1/2" BSP Vent Gauge	<b>OAB 3042</b>
6' x 1 1/2" BSP Vent Gauge	<b>OAB 3043</b>



### MTF 2000 CLOCK GAUGE

- FLOAT OPERATED
- NO POWER NEEDED
- EASY TO READ
- ADJUSTABLE TO SUIT TANK SIZE
- TOP MOUNT VIA 1 1/2" OR 2" BSP

0 - 100% Float Type 900-2000mm Range	<b>OAB 3320</b>
--------------------------------------	-----------------



### UNITEL & UNITOP HYDROSTATIC TANK GAUGES

FITS 900 - 3000MM HIGH CYLINDRICAL OR RECTANGULAR TANKS.

PERCENTAGE % FACES

Unitel c/w 10 mtr Capillary Tubing	<b>OAB 4000</b>
Unitel c/w 20 mtr Capillary Tubing	<b>OAB 4020</b>
Unitop Litre Calibrated Face (Heights or Diameters 3-4 Metres)	<b>OAB 3318</b>



### NORMOND HYDROSTATIC GAUGES

FOR TANKS UP TO 3 MTR DEEP. 'C' SERIES 6" CALIBRATED GAUGE INCLUDES 10 MTR OF CAPILLARY TUBING AND PROBE.

FOR TANKS 3-9 MTR DEEP, RIGID BALANCE CHAMBERS ARE RECOMMENDED - PRICE ON APPLICATION

Normond "C" Series 6" Calibrated in Litres	<b>OAB 6000</b>
Normond "E" Series 6" - % Low	<b>OAB 6001</b>
Normond "E" Series 6" - % Medium	<b>OAB 6001M</b>
Normond "E" Series 6" - % High	<b>OAB 6001H</b>