

Fuel – Reconnectable

- Instant closing, dual poppet check valve
- Retain UL approval after reconnection
- Shock absorbing spring to reduce nuisance breaks
- Dry reconnect o-ring to prevent fuel spill when reconnecting
- Separates at less than 200 lbs / 889.6 N to minimise backlash force of separation, reducing damage to equipment
- ATEX approved version of 1" model



Code	Description	Inlet/Outlet	Body	Fluids
HU-3385	Husky 3/4" Reconnectable Safe-T-Break®	3/4" F BSP	Aluminium	Diesel, Biodiesel
HU-3076	Husky 1" Reconnectable Safe-T-Break®	1" F BSP	Aluminium	Diesel, Biodiesel
HU-3076A	Husky 1" Reconnectable Safe-T-Break® ATEX	1" F BSP	Aluminium	Diesel, Biodiesel, Petrol

Fuel – Non-Reconnectable

- Instant closing, dual poppet check valve
- Lightweight, inexpensive and disposable after initial break
- Separates at less than 300 lbs / 1334.4 N
- ATEX approved version of 3/4" model



Code	Description	Inlet/Outlet	Body	Fluids
HU-2774	Husky 3/4" Non-Reconnectable Safe-T-Break®	3/4" F BSP	Zinc Alloys and Aluminium	Diesel, Biodiesel
HU-2774A	Husky 3/4" Non-Reconnectable Safe-T-Break® ATEX	3/4" F BSP	Zinc Alloys and Aluminium	Diesel, Biodiesel, Petrol
HU-6914	Husky 1" Non-Reconnectable Safe-T-Break®	1" F BSP	Zinc Alloys and Aluminium	Diesel, Biodiesel

AdBlue™ – Reconnectable

- Instant closing, dual poppet check valve
- 100% AdBlue™ compatible parts
- Separates at less than 200 lbs / 889.6 N to minimise backlash force of separation, reducing damage to equipment
- Comes as standard with scuff guard



Code	Description	Inlet/Outlet	Body	Fluids
HU-8216	Husky 1" Reconnectable Safe-T-Break® AdBlue™	1" M BSP	Stainless Steel	AdBlue™