

X-Mate

60lpm, 3/4" F BSP

The Husky ranges' entry level automatic shut off nozzle, designed for the safe and efficient refuelling of small commercial vehicles and passenger cars.

- Two versions available; a smaller OD model for refuelling vehicles with difficult fill points and a larger OD model for standard applications.
- Stream Shaper® as standard on the smaller spout version, and can be fitted to the larger spout version by purchasing the optional Stream Shaper replacement spout.
- Flo-stop® device for shutting off flow when spout is raised above the horizontal or falls out the tank
- One piece metal casting for enhanced durability with mate (half) scuff guard



Code	Description	Max Flow Rate (lpm)	Max Pressure (bar)	Spout OD (mm)	Inlet	Stream Shaper
HU-E159416-04	Husky X-Mate Nozzle Small OD UL	53	3.5	20.6	3/4" F BSP	•
HU-E159416-04-SW	Husky X-Mate Nozzle Small OD UL	53	3.5	20.6	1" F BSP Swivel	•
HU-E159415-04	Husky X-Mate Nozzle Large OD LDD	60	3.5	23.8	3/4" F BSP	
HU-E159415-04-SW	Husky X-Mate Nozzle Large OD LDD	60	3.5	23.8	1" F BSP Swivel	
HU-8862	Stream Shaper LDD Spout Assembly			23.8		•